

28 shall be attached to the vehicle, one in the front and the other in the rear.

29 (2) The license plate issued for a motorcycle, trailer, or semitrailer shall be attached to
30 the rear of the motorcycle, trailer, or semitrailer.

31 (3) ~~Every~~ Except as provided in Subsection (5), a license plate shall at all times be:

32 (a) securely fastened:

33 (i) in a horizontal position to the vehicle for which it is issued to prevent the plate from
34 swinging;

35 (ii) at a height of not less than 12 inches from the ground, measuring from the bottom
36 of the plate; and

37 (iii) in a place and position to be clearly visible; and

38 (b) maintained:

39 (i) free from foreign materials; and

40 (ii) in a condition to be clearly legible.

41 (4) Enforcement by a state or local law enforcement officer of the requirement under
42 Subsection (1) to attach a license plate to the front of a vehicle shall be only as a secondary
43 action when the vehicle has been detained for a suspected violation by any person in the
44 vehicle of Title 41, Motor Vehicles, other than the requirement under Subsection (1) to attach a
45 license plate to the front of the vehicle, or for another offense.

46 (5) The provisions of Subsections (3)(a)(iii) and (3)(b) do not apply to a license plate
47 that is obscured exclusively by one or more of the following devices or by the cargo the device
48 is carrying, if the device is installed according to manufacturer specifications or generally
49 accepted installation practices:

50 (a) a trailer hitch;

51 (b) a wheelchair lift or wheelchair carrier;

52 (c) a trailer being towed by the vehicle;

53 (d) a bicycle rack, ski rack, or luggage rack; or

54 (e) a similar cargo carrying device.

Legislative Review Note
as of 2-2-15 11:43 AM

Office of Legislative Research and General Counsel