

28 *Be it enacted by the Legislature of the state of Utah:*

29 Section 1. Section **41-6a-804** is amended to read:

30 **41-6a-804. Turning or changing lanes -- Safety -- Signals -- Stopping or sudden**
31 **decrease in speed -- Signal flashing -- Where prohibited.**

32 (1) (a) A person may not turn a vehicle, enter a roadway, merge into a continuing lane
33 from a lane of travel that is ending, or otherwise move right or left on a roadway or change
34 lanes until:

- 35 (i) the movement can be made with reasonable safety; and
- 36 (ii) an appropriate signal has been given as provided under this section.

37 (b) A signal of intention to turn right or left or to change lanes shall be given
38 continuously for at least the last two seconds preceding the beginning of the movement.

39 (2) A person may not stop or suddenly decrease the speed of a vehicle without first
40 giving an appropriate signal to the operator of any vehicle immediately to the rear when there is
41 opportunity to give a signal.

42 (3) (a) A stop or turn signal when required shall be given either by the hand and arm or
43 by signal lamps.

44 (b) If hand and arm signals are used, a person operating a vehicle shall give the
45 required hand and arm signals from the left side of the vehicle as follows:

- 46 (i) left turn: hand and arm extended horizontally;
- 47 (ii) right turn: hand and arm extended upward; and
- 48 (iii) stop or decrease speed: hand and arm extended downward.

49 (c) (i) A person operating a bicycle or device propelled by human power may give the
50 required hand and arm signals for a right turn by extending the right hand and arm horizontally
51 to the right.

52 (ii) This Subsection (3)(c) is an exception to the provision of Subsection (3)(b)(ii).

53 (4) A person required to make a signal under this section may not flash a signal:

- 54 (a) on one side only on a disabled vehicle;
- 55 (b) as a courtesy or "do pass" to operators of other vehicles approaching from the rear;

56 or

57 (c) on one side only of a parked vehicle.

58 (5) A violation of this section is an infraction.

59 Section 2. Section **41-6a-1635** is amended to read:

60 **41-6a-1635. Windshields and windows -- Tinting -- Obstructions reducing**
61 **visibility -- Wipers -- Prohibitions.**

62 (1) Except as provided in Subsections (2) [~~and~~], (3), and (4) a person may not operate a
63 motor vehicle with:

64 (a) a windshield that allows less than 70% light transmittance;

65 (b) a front side window that allows less than 43% light transmittance;

66 (c) any windshield or window that is composed of, covered by, or treated with any
67 material or component that presents a metallic or mirrored appearance; [~~or~~]

68 (d) any sign, poster, or other nontransparent material on the windshield or side
69 windows of the motor vehicle except:

70 (i) a certificate or other paper required to be so displayed by law; or

71 (ii) the vehicle's identification number displayed or etched in accordance with rules
72 made by the department under Section [41-6a-1601](#)[-]; or

73 (e) any debris, frost, or other substance that materially obstructs the operator's view.

74 (2) (a) A person may not operate a motor vehicle with an object or device hanging or
75 mounted in a manner that materially obstructs the operator's view.

76 (b) There is a rebuttable presumption that an object or device hanging or mounted in an
77 operator's field of view does not materially obstruct the operator's view if:

78 (i) the object or device obscures a zone no larger than 25 square inches; and

79 (ii) extends no more than seven inches:

80 (A) from the extreme outside left edge of the windshield;

81 (B) from the extreme outside right edge of the windshield; or

82 (C) in aggregate as measured from the center line of the windshield.

83 (c) A person shall ensure that an object or device hanging or mounted as described in
84 this Subsection (2) is used in accordance with this chapter.

85 [~~2~~] (3) Nontransparent materials may be used:

86 (a) along the top edge of the windshield if the materials do not extend downward more
87 than four inches from the top edge of the windshield or beyond the AS-1 line whichever is
88 lowest;

89 (b) in the lower left-hand corner of the windshield provided they do not extend more

90 than three inches to the right of the left edge or more than four inches above the bottom edge of
91 the windshield; or

92 (c) on the rear windows including rear side windows located behind the vehicle
93 operator.

94 [~~(3)~~] (4) A windshield or other window is considered to comply with the requirements
95 of Subsection (1) if the windshield or other window meets the federal statutes and regulations
96 for motor vehicle window composition, covering, light transmittance, and treatment.

97 [~~(4)~~] (5) Except for material used on the windshield in compliance with Subsections
98 [~~(2)~~] (3)(a) and (b), a motor vehicle with tinting or nontransparent material on any window
99 shall be equipped with rear-view mirrors mounted on the left side and on the right side of the
100 motor vehicle to reflect to the driver a view of the highway to the rear of the motor vehicle.

101 [~~(5)~~] (6) (a) (i) The windshield on a motor vehicle shall be equipped with a device for
102 cleaning rain, snow, or other moisture from the windshield.

103 (ii) The device shall be constructed to be operated by the operator of the motor vehicle.

104 (b) A windshield wiper on a motor vehicle shall be maintained in good working order.

105 [~~(6)~~] (7) A person may not have for sale, sell, offer for sale, install, cover, or treat a
106 windshield or window in violation of this section.

107 [~~(7)~~] (8) Notwithstanding this section, any person subject to the federal Motor Vehicle
108 Safety Standards, including motor vehicle manufacturers, distributors, dealers, importers, and
109 repair businesses, shall comply with the federal standards on motor vehicle window tinting.

110 [~~(8)~~] (9) A violation of this section is an infraction.